

PRODUCT FICHE

Energy Label Directive EU2010/30/EU-No65/2014 of range hoods

| | |
|--|------------------|
| Brand | ALTUS |
| Model | ALA 516 W |
| Mass of the appliance(M) (Net Weight) kg | 9,00 |
| Annual Energy Consumption(AEC hood)(kWh/a) | 56,0 |
| Energy Efficiency Class | B |
| Fluid Dynamic Efficiency (FDE hood) | 21,0 |
| Fluid Dynamic Efficiency Class | C |
| Lighting Efficiency (LE hood) (lux/watt) | 39,0 |
| Lighting Efficiency Class | A |
| Grease Filtering Efficiency | 55,5 |
| Grease Filtering Efficiency Class | E |
| Air flow (m³/h) (min. and max. setting) | 220-400 |
| Air flow (m³/h) (boost setting) | - |
| Sound power level (dB) (min. and max. setting) | 46-59 |
| Sound power level (dB) (boost setting) | - |
| Measured power consumption in standby mode (Ps) (W) | - |
| Measured power consumption off mode (Po)(W) | - |

7704331281 185733023 AA en_US

INSTRUCTION BOOKLET**Information for domestic range hoods**

Comply with EU directive 2009/125/EC Regulation No 66/2014

| | |
|---|------------------|
| Brand | ALTUS |
| Model | ALA 516 W |
| Annual Energy Consumption(AEC hood)(kWh/a) | 56,0 |
| Time increase factor (f) | 1,3 |
| Fluid Dynamic Efficiency (FDE hood) | 21,0 |
| Energy Efficiency Index (EEI hood) | 68,0 |
| Measured air flow rate at best efficiency point (QBEP) (m³/h) | 240,0 |
| Measured air pressure at best efficiency point (PBEP) (Pa) | 350,0 |
| Maximum air flow (Q max) (m³/h) | 400 |
| Measured electric power input at best efficiency point(WBEP) (W) | 115,0 |
| Nominal power of the lighting system (WL)(W) | 6,7 |
| Average illumination of the lighting system on the cooking surface (E middle)(lux) | 260,0 |
| Measured power consumption in standby mode (Ps) (W) | - |
| Measured power consumption off mode (Po)(W) | - |
| Sound power level (LWA)(dB) | 59 |

7704331281 185733023 AA en_US